

# MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.	<b>HMIS HAZARD RATING</b>
SAFETEC OF AMERICA	HEALTH <span style="margin-left: 100px;">0</span> <span style="margin-left: 100px;">0 = INSIGNIFICANT</span> <span style="margin-left: 100px;">3 = HIGH</span>
	FLAMMABILITY <span style="margin-left: 100px;">3</span> <span style="margin-left: 100px;">1 = SLIGHT</span> <span style="margin-left: 100px;">4 = EXTREME</span>
	REACTIVITY <span style="margin-left: 100px;">0</span> <span style="margin-left: 100px;">2 = MODERATE</span>
<b>TRANSPORTATION INFORMATION</b>	
PROPER SHIPPING NAME <span style="margin-left: 20px;">Solids containing flammable liquid, n.o.s.(Ethanol)</span>	
HAZARD CLASS / PKG. GRP. <span style="margin-left: 20px;">4.1 / II</span> <span style="margin-left: 20px;">IATA (non-canister)</span> <span style="margin-left: 20px;">Special Provision A46</span>	
IDENTIFICATION NUMBER <span style="margin-left: 20px;">UN317</span> <span style="margin-left: 20px;">US DOT (non-canister)</span> <span style="margin-left: 20px;">Special Provision 47</span>	<span style="margin-left: 20px;">5</span>

## SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST)  <b>p.a.w.s.</b>	Page 1 of 2
MANUFACTURER'S NAME Safetec of America, Inc.	EMERGENCY TELEPHONE NUMBER (24 Hours) (800) 255-3924
ADDRESS (NUMBER, STREET, P.O. BOX) 887 Kensington Avenue @ William L. Gaiter Pkwy.	TELEPHONE NUMBER FOR INFORMATION (716) 895-1822
(CITY, STATE AND ZIP CODE) Buffalo, NY 14215	DATE PREPARED <span style="float: right;">February 11, 2009</span> SUPERSEDES <span style="float: right;">November 21, 2007</span>

## SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))	CAS #	% (wt.) (OPTIONAL)	OSHA PEL/STEL		ACGIH TLV/TWA/STEL	
			PPM	MG/M <sup>3</sup>	PPM	MG/M <sup>3</sup>
Ethyl Alcohol	64-17-5	60 - 73	1000 (PEL)		1000 (TLV)	

This product is not known to contain a substance subject to Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR 372 at or above minimal amounts.

## SECTION 3 - HEALTH HAZARD DATA

ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE	EMERGENCY AND FIRST AID PROCEDURES
INHALATION: Brief (minutes) inhalation will not cause adverse effects, although, constant inhalation may cause irritation to upper respiratory tract.	Remove to fresh air; provide oxygen if breathing is difficult; seek medical attention if required.
EYES: Brief contact to gel or vapors may cause mild irritation; prolonged contact may cause moderate irritation associated with redness.	Flush eyes with clear running water for a minimum of 15 minutes while holding eyelids open; if irritation persists, seek medical attention.
INGESTION: Small amounts swallowed incidental to normal handling are not likely to cause injury. Swallowing larger amounts may cause injury.	DO NOT induce vomiting; seek immediate medical attention. Vomiting may be induced only under the supervision of a physician.

HEALTH HAZARDS (ACUTE AND CHRONIC): Acute effects are possible irritation and discomfort; no known chronic effects have been established.

CARCINOGENICITY	NTP?	No	IARC MONOGRAPHS?	No	OSHA REGULATED?	No
No additional information						

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting skin, eye, or respiratory disorders may become aggravated through prolonged exposure.

**MATERIAL SAFETY DATA SHEET**

IDENTITY (AS USED ON LABEL AND LIST)

p.a.w.s.

Page 2 of 2

Date: November 21, 2007

**SECTION 4 - FIRE FIGHTING MEASURES**

FLASH POINT (METHOD USED) 81°F (TOC)	FLAMMABLE LIMITS (% Volume in Air for Lowest Flashing Component) LEL: 3.3 UEL: 19
---	--

**EXTINGUISHING MEDIA**Dry chemicals, alcohol-type or all-purpose foam, CO<sub>2</sub>**SPECIAL FIRE FIGHTING PROCEDURES**

Use water spray to cool fire-exposed containers and structures. Use water spray to disperse vapors; re-ignition is possible

**UNUSUAL FIRE AND EXPLOSIVE HAZARDS**

Flammable gel. Toxic gases (such as carbon monoxide and formaldehyde) may be released in a fire. Concentrated vapors may be flammable.

**SECTION 5 - PRECAUTIONS FOR SAFE HANDLING AND USE / LEAK PROCEDURES****STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED**

Remove all sources of ignition. Small spills may be flushed with large amounts of water; larger spills should be collected for disposal.

**WASTE DISPOSAL METHODS**

Dispose of in accordance with Local, State, and Federal regulations. Products classified as non-hazardous may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260-299" for complete waste disposal regulations. Consult your Local, State, or Federal Environmental Protection Agency before disposing of any chemicals.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Keep container(s) tightly closed when not in use. Avoid inhalation of high concentration of vapors. Store in cool, dry area away from possible sources of ignition. Keep this and other chemicals out of reach of children.

**SECTION 6 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

RESPIRATORY PROTECTION Ordinarily, none required	VENTILATION LOCAL EXHAUST: Required MECHANICAL (GENERAL): Yes
PROTECTIVE GLOVES Ordinarily, none required	EYE PROTECTION Ordinarily, none required
OTHER PROTECTIVE CLOTHING OR EQUIPMENT Ordinarily, none required	WORK / HYGIENIC PRACTICES Practice safe work habits. Use according to label instructions.

**SECTION 7 - PHYSICAL / CHEMICAL PROPERTIES**

BOILING POINT 173.8°F	SPECIFIC GRAVITY (WATER = 1) 0.886
VAPOR PRESSURE (mm Hg) No data	MELTING POINT Not applicable
VAPOR DENSITY (AIR = 1) 1.59 (ALC.)	pH 6 - 8
SOLUBILITY IN WATER Moderate	EVAPORATION RATE (n-BUTYL ACETATE = 1) 1.7 (ALC.)
APPEARANCE AND ODOR Clear liquid	% VOLATILES (BY WEIGHT) > 99

**SECTION 8 - STABILITY AND REACTIVITY**

STABILITY UNSTABLE: STABLE: XXX	CONDITIONS TO AVOID Extreme temperatures; sources of ignition
INCOMPATIBILITIES (MATERIALS TO AVOID) Strong oxidizers; strong acids	
HAZARDOUS DECOMPOSITION OR BYPRODUCTS Decomposition will not occur if handled / stored properly. Thermal decomposition may emit typical products of combustion.	
HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: XXX	CONDITIONS TO AVOID Heat

The information contained herein is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.